



## RAVENOL CVT Fluid



ART.-NR. 1211110

1 L | 1211110-001  
4 L | 1211110-004  
10 L | 1211110-010  
20 L | 1211110-020  
20 L | 1211110-B20  
60 L | 1211110-060  
60 L | 1211110-D60  
208 L | 1211110-208  
208 L | 1211110-D28  
1000 L | 1211110-700

### FABRICATION SYNTHETIC

**RECOMMENDATIONS** VW/AUDI G052180 A2 | VW/AUDI G052180 A6 | BMW CVT EZL 799A | FORD EU WSS-M2C928-A | FORD FOCUS C-MAX CFT23 | FORD USA WSS-M2C933-A | FORD XT-7-QCFT FREESTYLE | FORD FIVE HUNDRED CFT30 | HMMF ULTRA FLUID 08260-99904 | HMMF ULTRA FLUID 08260-99907 | HONDA CVT FLUID 08200-9006 | MB 236.20 A 0019894603 | MAZDA TFF CVT FLUID TC JWS3320 K020-W0-051W | NISSAN CVT FLUID NS-1 | NISSAN KLE50 00002 | NISSAN KLE50 00004 | OPEL/GM 1940713 | SUBARU I-CVT FLUID K0415-YA090 | SUZUKI S-CVT 99000-22801-000 | TOYOTA CVT FLUID TC 08886-02105 | VW/AUDI G052180 A1 | VW/AUDI TL 52180 | VW G052516 A2 | MINI COOPER CVT

**RAVENOL CVT Fluid** is a synthetic ATF for the latest generation of CVT transmission.

**RAVENOL CVT Fluid** guarantees an optimum of power transmission.

**RAVENOL CVT Fluid** is based on high-quality hydrocrack oils with special additives and inhibition to ensure the proper operation of the automatic transmission.

## Application Notes

**RAVENOL CVT Fluid** was developed for use in CVT transmission (Steel Belt Continuously Variable Transmission).

**RAVENOL CVT Fluid** ensures a stable viscosity under high mechanical stress in the transmission elements (push belt).

## Characteristics

**RAVENOL CVT Fluid** offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- Neutral behaviour towards sealing materials
- Neutral behaviour by inhibition to non-ferrous metals



RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the

product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to

malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	838,0	EN ISO 12185
Colour		gelb	visual
Pourpoint	°C	-51	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. January 2020