



## RAVENOL CVT KFE Fluid



**FABRICATION SYNTHETIC**

**RECOMMENDATIONS TOYOTA 08886-02503 | TOYOTA 08886-02505**

**RAVENOL CVT KFE Fluid** is a synthetic CVT (Continuously Variable Transmission) Fluid, designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the transmission.

**ART.-NR. 1211134**

**RAVENOL CVT KFE Fluid** is a synthetic CVT transmission fluid with low viscosity for Toyota CVT transmission.

1 L | 1211134-001

4 L | 1211134-004

20 L | 1211134-020

20 L | 1211134-B20

1000 L | 1211134-700

**RAVENOL CVT KFE Fluid** guarantees an optimum of power Transmission.

## Application Notes

**RAVENOL CVT KFE Fluid** was developed for use in CVT transmission (Steel Belt Continuously Variable Transmission), especially for Toyota transmissions.

**RAVENOL CVT KFE Fluid** ensures a stable viscosity under high mechanical stress in the transmission elements (push belt).

## Characteristics

**RAVENOL CVT KFE Fluid** offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- Neutral behaviour towards sealing materials
- Neutral behaviour by inhibition to non-ferrous metals

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the

product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult



our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	829,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-51	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 22. August 2019