RAVENOL Diesel System Cleaner

ART.-NR. 1390243

300 ml | 1390243-300

RECOMMENDATIONS REINIGT DAS EINSPRITZSYSTEM UND STELLT DIE VOLLE LEISTUNG DES MOTORS WIEDER HER

Fuel additive for all diesel engines.

RAVENOL Diesel System Cleaner is a fuel additive for all diesel engines for cleaning the diesel system, increasing operational safety and for the economic feasibility of diesel engines.

RAVENOL Diesel System Cleaner is a cleaning agent for electronically and mechanically controlled fuel injectors.

RAVENOL Diesel System Cleaner provides for a cleaned injection system and therefore, for a combustion with a low degree of soot and reduced particles.

RAVENOL Diesel System Cleaner prevents rattling noises and rough idling.

Application Notes

RAVENOL Diesel System Cleaner is added to the diesel fuel.

Area of application:

- Diesel engines in passenger cars and lorries
- Can be used preventively at every service, in particular prior to emission measurements
- In the event of reduced engine performance
- For all repairs on diesel injection systems
- Can also be used in bio-diesel or mixtures of diesel fuel with bio-diesel

Application: The cleaning process is carried out in the tank or by filling the filter.

Cleaning process using the tank: Can content is sufficient for approx. 80 liters of diesel fuel. (Mixing ratio: 1: 250). Fill the appropriate amount depending on the tank filling. Repeat after 2000 km.

Cleaning process using the filter housing: It is imperative to renew the filter! Completely fill the filter housing with **RAVENOL Diesel System Cleaner** and remove air. Cleaning period approx. 10 min. with alternating speed up to a max. of 2000 rpm.

Ravensberger Schmierstoffvertrieb GmbH | Jöllenbecker Str. 2 | 33824 Werther / Germany
Telefon: +49 5203 9719 0 | Telefax: +49 5203 9719 40 | E-Mail: kontakt@ravenol.de
www.ravenol.de

1/2

Characteristics

RAVENOL Diesel System Cleaner provides:

- Cleaning of the fuel injection system
- Precise fine atomisation of the diesel fuel
- Establishment of full engine power
- Reduction of smoke generation

Property	Unit	Data	Audit
Density at 20°C	kg/m³	839	EN ISO 12185
Colour		hellbraun	visual
Flash Point PM	°C	62	DIN ISO 3679

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. January 2020

Ravensberger Schmierstoffvertrieb GmbH | Jöllenbecker Str. 2 | 33824 Werther / Germany
Telefon: +49 5203 9719 0 | Telefax: +49 5203 9719 40 | E-Mail: kontakt@ravenol.de
www.ravenol.de

2/2