



RAVENOL Fork Oil Medium 10W



VISCOSITY 10W

FABRICATION MINERAL

RECOMMENDATIONS YAMAHA | KAWASAKI | HONDA | APRILIA | BMW | SUZUKI | DUCATI | TRIUMPH | MOTO-GUZZI

RAVENOL Fork Oil Medium 10W is a fork oil on mineral oil base which was developed for all forks of off-road motorbikes and motor cross bikes.

ART.-NR. 1182104

1 L | 1182104-001
4 L | 1182104-004
20 L | 1182104-020
20 L | 1182104-B20
1000 L | 1182104-700

RAVENOL Fork Oil Medium 10W is especially characterised by a high and stable viscosity index as well as a solid corrosion protection. Efficient additives offer even under extreme loads an excellent corrosion protection. The behaviour against sealing materials is neutral.

Application Notes

RAVENOL Fork Oil Medium 10W was developed for the use in all chassis components of two-wheeler vehicles and offers good power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the mineral fork oils are miscible among each other.

Characteristics

RAVENOL Fork Oil Medium 10W offers:

- good damping characteristics at all temperatures
- a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics
- a very low pour point

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	851,0	EN ISO 12185
Colour		gelb	visual
Viscosity at 100°C	mm ² /s	6,6	DIN 51 562



Property	Unit	Data	Audit
Viscosity at 40°C	mm ² /s	32,8	DIN 51 562
Viscosity index VI		162	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash point (COC)	°C	210	DIN ISO 2592
TBN	mg KOH/g	0,4	ASTM D2896
Sulphated ash	%wt.	ca. 0,06	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 08. August 2019