



## RAVENOL Diesel Performance Optimizer Premium



ART.-NR. 1390241

300 ml | 1390241-300

**RAVENOL Diesel Performance Optimizer Premium** is a premium fuel additive for all diesel engines for cleaning the diesel system, increasing operational safety and for the economic feasibility of diesel engines.

**RAVENOL Diesel Performance Optimizer Premium** reduces CO<sub>2</sub> and HC emissions, which is tested and certified by the TÜV (Technical Inspection Agency) Thuringia.

**RAVENOL Diesel Performance Optimizer Premium** cleans the diesel system and the combustion chamber; this leads to a clean fuel injection system.

**RAVENOL Diesel Performance Optimizer Premium** enables saving fuel. The formation of “acidic” water is prevented and therefore, there is a higher level of protection against corrosion.

**RAVENOL Diesel Performance Optimizer Premium** increases the lubrication effect for low sulphur fuel.

**RAVENOL Diesel Performance Optimizer Premium** prolongs the service life of catalytic converters and lambda probes by means of optimum combustion.

## Application Notes

**RAVENOL Diesel Performance Optimizer Premium** is added to the diesel fuel.

Area of application:

- Diesel engines in passenger cars and lorries
- Can be used preventively at every service
- For all diesel fuels, summer and winter diesel
- Suitable for modern common rail and pump nozzle systems
- Can also be used in bio-diesel or mixtures of diesel fuel with bio-diesel

Application: Pour the contents of the container into the tank. Fuel volume up to 50 litres of diesel. Minimum fuel capacity according to volume of fuel reserve.

## Classifications

**RAVENOL Diesel Performance Optimizer Premium** is an easy to mix diesel additive.

The efficacy of the CO<sub>2</sub> and HC emissions is tested and certified by the TÜV (Technical Inspection Agency) Thuringia.



## Characteristics

RAVENOL Diesel Performance Optimizer Premium offers:

- Certified efficacy by the TÜV (Technical Inspection Agency) Thuringia for the reduction of CO<sub>2</sub> and HC emissions.
- Cleans diesel system and combustion chamber
- Saves fuel
- No "acidic" water, corrosion protection
- Increases the lubrication effect for low sulphur fuel
- Improves the ignitability and reduces "rattling sounds" caused by fuel

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	842,0	EN ISO 12185
Colour		braun	visual
Flash Point PM	°C	45	DIN ISO 3679

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 24. October 2019