





RAVENOL Motogear SAE 10W-40 GL-4



ART.-NR. 1250101

1 L | 1250101-001 4 L | 1250101-004 VISCOSITY 10W-40 SPECIFICATIONS API GL-4 |SAE 10W-40 FABRICATION SEMI-SYNTHETIC

RAVENOL MOTOGEAR SAE 10W-40 GL-4 is a special multi-range transmission fluid on the basis of synthetic technology and special esters specifically formulated for easy gear changing even under extremely hard operating conditions.

RAVENOL MOTOGEAR SAE 10W-40 GL-4 is used in 2- and 4-stroke engines with separate gear lubrication and wet clutch systems.

RAVENOL MOTOGEAR SAE 10W-40 GL-4 enables a precise and soft changing of gears. Prevents clutch slippage. Forms a heavy-duty lubricant film, which is effective under all operating conditions.

RAVENOL MOTOGEAR SAE 10W-40 GL-4 is used in motorcycles from Japanese and European manufacturers.

Application Notes

RAVENOL MOTOGEAR SAE 10W-40 GL-4 is used in 2- and 4-stroke engines with separate gear lubrication and wet clutch systems.

RAVENOL MOTOGEAR SAE 10W-40 GL-4 enables a precise and soft changing of gears. Prevents clutch slippage. Forms a heavy-duty lubricant film, which is effective under all operating conditions.

Characteristics

RAVENOL Motogear SAE 10W-40 GL-4 offers:

- Quick lubrication of the engine at all operating temperatures.
- Heavy-duty lubricant film under all operating conditions.
- Precise, soft changing of gears, no clutch slippage.
- Reliability due toexcellent lubricant film adhesion, extraordinary purification capacity and outstanding ageing resistance.
- Neutral towards sealing compounds.







Property	Unit	Data	Audit
Density at 20°C	kg/m³	862	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm²/s	14,0	DIN 51 562
Viscosity at 40°C	mm²/s	91,3	DIN 51 562
Viscosity index VI		157	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flash point (COC)	°C	238	DIN ISO 2592
TBN	mg KOH/g	9,5	ASTM D2896
Sulphated ash	%wt.	1,5	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 28. November 2019