



- 1 L | 1212106-001
- 4 L | 1212106-004
- 10 L | 1212106-010
- 20 L | 1212106-020
- 60 L | 1212106-060
- 208 L | 1212106-208
- 1000 L | 1212106-700

RAVENOL DCT/DSG GETRIEBE FLUID

Category Gear oil for automatic transmissions

Item number 1212106

Oil type Synthetic

Recommendation Audi G052529 A2 S-Tronic, BMW 83220440214, BMW 83222147477, BMW 83222148578, BMW 83222148579, BMW 83222446673, BMW DCTF-1, BOT 341, Chrysler 68044345 EA, Citroën/Peugeot 9734.S2 für DCS6, Drexler DSG-Getriebe mit Miba-Carbon-Lamelle, Fiat 9.55550-MZ6 für TCT (Twin Clutch Transmission, Ford 1490761, Ford 1490763, Ford USA XT-11-QDC, Ford WSD-M2C200-D2, Ford WSS-M2C936-A, MB 236.21, Mitsubishi Dia Queen SSTF-I, Mitsubishi MZ320065, Renault EDC (Efficiency Dual Clutch System), VOLVO 1161838, VOLVO 1161839, VW G 052 182 A2, VW G 052 513, VW G 055 529 A2

Application Passenger car

RAVENOL DCT/DSG Getriebe Fluid is a synthetic DCT (Dual Clutch Transmission) Fluid, designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the dual clutch transmission.

RAVENOL DCT/DSG Getriebe Fluid guarantees good lubricating properties even at extremely temperatures in summer and low winter temperatures.

RAVENOL DCT/DSG Getriebe Fluid allows virtually slip-free operation and thus minimal torque losses. Ensures low wear and long life of the transmission. Fuel economy.

Application Note

RAVENOL DCT/DSG Getriebe Fluid has been developed especially for Dual Clutch Gear of several manufacturers like VW/Audi, Ford, Volvo, Chrysler, Dodge, Mitsubishi and others.

RAVENOL DCT/DSG Getriebe Fluid is also recommended for use in Dual Clutch Gear DQ-250 (02E) and DQ-500 (0BT) acc. to VW Part-No. G 052 182 and DL-501 (0B5) acc. to VW Part-No. G 052 529 for S-Tronic of VW, Audi, Seat and Skoda.

RAVENOL DCT/DSG Getriebe Fluid is recommended by Fa. Drexler for all DCG-transmissions with MibaCarbon plates.

Characteristics

- Good lubricating properties also at low

temperatures in winter

- Stable lubricant film even under extreme loads in summer
- Low wear
- Excellent viscosity-temperature behaviour
- Very low pour point
- Low foaming even under heavy demands
- Extensive protection against wear, corrosion and foaming
- Neutral behavior towards sealing materials

Technical Product Data

Density at 20 °C	840,0	kg/m ³	EN ISO 12185
Colour	gelbbraun		VISUELL
Pourpoint	-51	°C	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

28.02.2022