



1.5 L | 1410119-150
5 L | 1410119-005
10 L | 1410119-010
20 L | 1410119-020
60 L | 1410119-060
208 L | 1410119-208
1000 L | 1410119-700

RAVENOL HTC HOT CLIMATE -15°C PROTECT MB 325.0

Category Radiator antifreeze

Item number 1410119

Recommendation ASTM D3306, ASTM D4340, ASTM D4985, Audi, BMW 83192211191, DAF, Ford AF Plus, Ford ESE-M978B4H-A, GM 1825M, GM 1899M, GM 93740140, GM 93740141, GM SATURN, Honda OL999-9011, Jaguar, John Deere, MAN 324, MB (A 000 989 08 25 10), MB 325.0 (Konzentrat), MB 326.0 (Premix), NATO S-759, Opel/GM QL130100, Porsche, Renault Glaceol RX Type D, ROVER, SAAB, SAE J1034, VW TL 774-C (entspricht G11)

Application Passenger car, Agricultural machinery

RAVENOL HTC Hybrid Tech. Coolant HOT

CLIMATE -15°C is a ready-to-use, prediluted with water, eco-friendly, 1.2- Ethanediol (monoethylene glycol) based amine and phosphate-free, all-season coolant with frost and rust protection for Mercedes, BMW, Opel, Saab and General Motors engines. This product is formulated based on a proven inhibitor development by combining silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL HTC Hybrid Tech. Coolant HOT

CLIMATE -15°C protects the cooling system from rust, frost, and in summer, from overheating.

Application Note

RAVENOL HTC Hybrid Tech. Coolant HOT

CLIMATE -15°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL HTC Hybrid Tech. Coolant HOT CLIMATE -15°C** to radiator to fill line.

Characteristics

- Excellent for use in cast iron or aluminium engines, or alloys of the two metals, and

aluminium and copper alloy radiators

- Good reserve alkalinity
- Protection from corrosion and cavitation
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators

Technical Product Data

Density at 20 °C	1040,0	kg/m ³	EN ISO 12185
Colour	blau		VISUELL
pH - value at 20 °C	7,5		ASTM D1287
Freezing point	-15	°C	ASTM D1177

All indicated data are approximate values and are subject to the commercial fluctuations.

23.02.2022