



1 L | 1211114-001  
4 L | 1211114-004  
10 L | 1211114-010  
20 L | 1211114-020  
20 L | 1211114-B20  
60 L | 1211114-060  
60 L | 1211114-D60  
208 L | 1211114-208  
208 L | 1211114-D28

## RAVENOL CVTF NS2/J1 FLUID

**Category** Gear oil for automatic transmissions

**Item number** 1211114

**Oil type** Synthetic

**Recommendation** Mitsubishi S0001401, Nissan CVT NS-2, Nissan KLE52-0002, Nissan KLE52-0004, PSA 9735EF, Suzuki CVT Fluid Green-1 99000-22B15-046

**Application** Passenger car

**RAVENOL CVTF NS2/J1 Fluid** is a synthetic CVTF (Continuously Variable Transmission Fluid) produced on the basis of high-quality hydrocrack oils with special additives and inhibition which guarantees a perfect function of the CVT transmission.

**RAVENOL CVTF NS2/J1 Fluid** is a CVTF of the latest generation. It is especially developed for the CVT transmission of JATCO. It guarantees in any mode for maximum wear protection.

**RAVENOL CVTF NS2/J1 Fluid** is green coloured.

### Application Note

**RAVENOL CVTF NS2/J1 Fluid** is suitable for use in CVT transmission of following vehicles with CVT-transmission: Peugeot 4007, Citroen C-Crosser, Mitsubishi Outlander, Mitsubishi Delica D5, Mitsubishi Galant Fortis, Mitsubishi RVR, Mitsubishi Lancer 1.8 CY0 2007, Nissan Murano, Nissan Teana, Nissan Maxima, Nissan Presage, Nissan X-Trail, Nissan Lafesta, Nissan Serena, Nissan Bluebird Sylphy, Nissan Dualis, Suzuki Kizachi, Suzuki SX4, Dodge Caliber, Jeep Compass, Jeep Patriot and other models with CVT-transmission JATCO JF011E (RE0F10A, F1CJA) or JF010E (RE0F09A). Maintenance-filling under normal operating conditions.

### Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

### Technical Product Data

Density at 20 °C	846,0	kg/m <sup>3</sup>	EN ISO 12185
Colour	grün		VISUELL
Pourpoint	-45	°C	DIN ISO 3016

**All indicated data are approximate values and are subject to the commercial fluctuations.**

28.02.2022