



1 L | 1211100-001
4 L | 1211100-004
10 L | 1211100-010
20 L | 1211100-020
20 L | 1211100-B20
60 L | 1211100-060
208 L | 1211100-208

RAVENOL ATF+4 FLUID

Category Gear oil for automatic transmissions

Item number 1211100

Oil type Synthetic

Approvals Chrysler License-No. 40630041 FCA US LLC

Recommendation Chrysler MS-9602, Fiat 9.55550-AV4, Mopar 68218054GA, Mopar 68218057GA, Mopar 68218058GA

Application Passenger car

RAVENOL ATF+4® Fluid is a synthetic, licensed automatic transmission fluid ATF with an unique additive package for Fiat-Chrysler, Jeep and Dodge automatic transmission.

RAVENOL ATF+4® Fluid guarantees maximum wear protection in all operating conditions.

RAVENOL ATF+4® Fluid is mixable with all ATF+4®, ATF+2® or ATF+3® transmission oil.

Application Note

RAVENOL ATF+4® Fluid is recommended for refilling and fill up automatic transmission oil for Fiat-Chrysler, Dodge, Plymouth, RAM, Jeep and Eagle vehicles with automatic transmission.

RAVENOL ATF+4® Fluid achieves the warranty of FCA US LLC (Fiat Chrysler Automobiles) and is released with Licence-No. 40630041.

RAVENOL ATF+4® Fluid meets the requirements of current and previous standards for Fiat-Chrysler, Dodge, Plymouth, Jeep and Eagle automatic transmission oil.

Characteristics

- Better protection and better performance than ATF+3®
- Extended transmission life
- Reduces maintenance costs
- Better shift quality through a consistent viscosity profile
- Better cold flow properties
- Smooth switching at low temperatures
- Less transmission wear when operating at low temperatures
- Better oxidation stability and thermal stability than the previous ATF+3®
- Longer oil life period
- Lower oil consumption

- Better fuel economy
- Longer oil change intervals (has been tested extensively with oil change intervals of about 160,000 km)

Technical Product Data

Density at 20 °C	845,0	kg/m ³	EN ISO 12185
Colour	rot		VISUELL
Viscosity at 100 °C	7,5	mm ² /s	DIN 51562-1
Viscosity at 40 °C	35,1	mm ² /s	DIN 51562-1
Viscosity Index VI	192		DIN ISO 2909
Pourpoint	-63	°C	DIN ISO 3016
Brookfield Viscosity at -40 °C	6.500	mPa*s	ASTM D2983
Flashpoint	198	°C	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

03.03.2022