



1 L | 1213102-001  
4 L | 1213102-004  
10 L | 1213102-010  
20 L | 1213102-020  
20 L | 1213102-B20  
208 L | 1213102-208  
208 L | 1213102-D28  
1000 L | 1213102-700

## RAVENOL ATF DEXRON D II

**Category** Gear oil for automatic transmissions

**Item number** 1213102

**Specification** Allison C3, Allison C4, GM Dexron®-IID

**Oil type** Mineral

**Approvals** Voith H55.6335.xx

**Recommendation** Caterpillar TO-2, CVT, Ford M2C-138 CJ, Ford M2C-166H, Ford M2C-185A, Ford MERCON®, Ford SQM-9010B, MAN 339 Z1, MB 236.6, MB 236.7, Renk Doromat, ZF TE-ML 03D, ZF TE-ML 04D, ZF TE-ML 05L, ZF TE-ML 11A, ZF TE-ML 14A, ZF TE-ML 17C

**Application** Passenger car, Truck, Oldtimer

**RAVENOL ATF Dexron D II** is a first class transmission fluid for automatic transmissions of all vehicles and working machines on the basis of high refined mineral oils with a corresponding additive treatment.

### Application Note

**RAVENOL ATF Dexron D II** was developed for the use in automatic transmissions, hydro steering mechanisms, converters and power transmissions and can be used as a universal ATF (Automatic-Transmission-Fluid) for all vehicles and working machines.

### Characteristics

- protection against corrosion, sludge and sticking
- an excellent and very shear stable viscosity temperature behaviour
- no problems concerning very low respectively very high temperatures
- an excellent high thermal capacity
- free of foam even under hardest loads
- neutral behaviour against sealing materials
- mixable and compatible with all kinds of ATF

### Technical Product Data

Density at 20 °C	848,0	kg/m <sup>3</sup>	EN ISO 12185
Colour	Rot		VISUELL
Viscosity at 100 °C	7,3	mm <sup>2</sup> /s	DIN 51562-1
Viscosity at 40 °C	34,3	mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	185		DIN ISO 2909
Pourpoint	-51	°C	DIN ISO 3016
Flashpoint	210	°C	DIN EN ISO 2592

**All indicated data are approximate values and are subject to the commercial fluctuations.**

03.03.2022