



0.1 L | 1340121-100
0.2 L | 1340121-200
0.4 L | 1340121-400
1 L | 1340121-001
5 L | 1340121-005
10 L | 1340121-010
15 L | 1340121-015
25 L | 1340121-025
180 L | 1340121-180

RAVENOL HOT RED GREASE HRG 2

Category Grease

Item number 1340121

Specification DIN 51502: KP2P-35, ISO 6743-9: ISO-L-XCEEB2

Approvals MAN 284 Li-H2, MB-Freigabe 265.1

Application Passenger car, Truck, Industry

RAVENOL Hot Red Grease HRG 2 is a red lithium complex soap lubricating grease on the basis of high quality base oils. Excellent work resistance, rust and corrosion protection. Application for the lubrication of roller and friction bearings under extreme pressure at high bearing temperatures. Particularly recommended for the lubrication of wheel bearings on commercial vehicles and for high-speed passenger car wheel bearings.

Application Note

RAVENOL Hot Red Grease HRG 2 is used for the lubrication of roller and friction bearings under extreme pressure at high bearing temperatures.

RAVENOL Hot Red Grease HRG 2 is particularly recommended for the lubrication of commercial vehicles and for high-speed passenger car wheel bearings.

Characteristics

- Work resistance
- Resistance to oxidation
- Water resistance
- Good corrosion protection characteristics
- High thermal load capacity
- High pressure susceptibility
- Good adhesion

Technical Product Data

Colour	rot		VISUELL
Thickener	Lithium-Komplexseifen		DIN 51757
NLGI-Class	2		DIN 51818
Product Classification	KP2P-35		DIN 51502
Working Temperature	-35 / +160	°C	DIN 51825
Short term temperature up to	200	°C	DIN 51757
Worked Penetration at 60 Strokes	265-295	mm/10/25°C	ISO 2137
Corrosion (SKF Emscor dist. Water)	0	Korr. Grad	DIN 51802
Dropping Point	>260	°C	DIN ISO 2176
Copper Corrosion (24h/120 °C)	1		DIN 51811
Water Resistance (3h/90 °C)	1-90	°C	DIN 51807-1
VKA Pressure Carrying Capacity	2600-2800	N	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	140	mm ² /s	DIN 51562-1

All indicated data are approximate values and are subject to the commercial fluctuations.

16.03.2022