



1 L | 1222102-001
4 L | 1222102-004
10 L | 1222102-010
20 L | 1222102-020
20 L | 1222102-B20
60 L | 1222102-060
60 L | 1222102-D60
208 L | 1222102-208
208 L | 1222102-D28
1000 L | 1222102-700

RAVENOL GETRIEBEOEL LS SAE 75W-90

Category Gear oil for manual transmissions and drive axis

Item number 1222102

Specification API GL-5 + LS, MIL-L-2105 D

Oil type Synthetic

Recommendation GM 1940058, GM 88862624, GM 88862625, GM 93165388, ZF TE-ML 05C, ZF TE-ML 05D

Application Passenger car, Truck

RAVENOL Getriebeoel LS SAE 75W-90 is a synthetic lubricant for mechanical transmissions.

RAVENOL Getriebeoel LS SAE 75W-90 is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

Application Note

RAVENOL Getriebeoel LS SAE 75W-90 was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

Characteristics

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties
- fuel savings

Technical Product Data

Density at 20 °C	870,0	kg/m ³	EN ISO 12185
Colour	gelb		VISUELL
Viscosity at 100 °C	17,1	mm ² /s	DIN 51562-1
Viscosity at 40 °C	118,3	mm ² /s	DIN 51562-1
Viscosity Index VI	158		DIN ISO 2909
Brookfield Viscosity at -40 °C	88.800	mPa*s	ASTM D2983
Pourpoint	-42	°C	DIN ISO 3016
Flashpoint	192	°C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1b		ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.
07.03.2022