



0.1 L | 1340101-100
0.2 L | 1340101-200
0.4 L | 1340101-400
1 L | 1340101-001
5 L | 1340101-005
10 L | 1340101-010
15 L | 1340101-015
25 L | 1340101-025
180 L | 1340101-180

RAVENOL MEHRZWECKFETT OML

Category Grease

Item number 1340101

Specification DIN 51502: K2K-30, ISO 6743-9: ISO-L-XCCEA2

Application Passenger car, Truck, Agricultural machinery, Industry

RAVENOL Mehrzweckfett OML is lithium saponified multipurpose grease with oxidation and corrosion protective additives.

RAVENOL Mehrzweckfett OML has an extreme mechanical stability and a very low friction value. Therefore it can be transported easily.

Application Note

RAVENOL Mehrzweckfett OML is used for the lubrication of easy loaded antifriction bearings and machine components. It is also suited as multipurpose lubrication grease for vehicles.

Characteristics

- Universal use, multipurpose characteristic for a mixed car pool
- Extreme shear stability
- Excellent corrosion protection
- Excellent wear protection
- Very good mechanical and chemical stability
- Very good aging resistant
- Good pumpability, even at low temperatures

Technical Product Data

Colour	hellbraun		VISUELL
Thickener	Lithium-Komplexseifen		DIN 51757
NLGI-Class	2		DIN 51818
Product Classification	K2K-30		DIN 51502
Working Temperature	-30 / +120	°C	DIN 51825
Kinematic Viscosity (Base Oil) at 40 °C	130	mm ² /s	DIN 51562-1
Worked Penetration at 60 Strokes	265-295	mm/10/25°C	ISO 2137
Corrosion (SKF Emscor dist. Water)	1	Korr. Grad	DIN 51802
Dropping Point	>180	°C	DIN ISO 2176
Copper Corrosion (24h/120 °C)	1		DIN 51811
Water Resistance (3h/90 °C)	1-90	°C	DIN 51807-1
VKA Pressure Carrying Capacity	2000 - 2200	N	DIN 51350-4
Short term temperature up to	130	°C	DIN 51757

All indicated data are approximate values and are subject to the commercial fluctuations.

10.03.2022