



1 L | 1222100-001
4 L | 1222100-004
10 L | 1222100-010
20 L | 1222100-020
20 L | 1222100-B20
60 L | 1222100-060
60 L | 1222100-D60
208 L | 1222100-208
208 L | 1222100-D28
1000 L | 1222100-700

RAVENOL GETRIEBEOEL PSA SAE 75W-80

Category Gear oil for manual transmissions and drive axis

Item number 1222100

Specification API GL-4

Oil type Semi-Synthetic

Recommendation PSA B71 2315

Application Passenger car

RAVENOL Getriebeoel PSA SAE 75W-80 is a high-quality solvent refined base oil based semi-synthetic multi-grade transmission oil with special EP (extreme pressure) properties.

RAVENOL Getriebeoel PSA SAE 75W-80 has a special formula for outstanding wear protection and lubrication properties.

Application Note

RAVENOL Getriebeoel PSA SAE 75W-80 is used in manual shift transmissions requiring trouble-free lubrication.

RAVENOL Getriebeoel PSA SAE 75W-80 can be used in manual transmissions where the manufacturer specifies a low-viscosity oil.

Characteristics

- Outstanding oxidation protection.
- Low viscosity in low temperatures.
- Excellent wear protection.
- Enhanced EP properties.
- Good foaming properties.
- Neutral to sealants.
- Outstanding protection from rust and corrosion.

Technical Product Data

Density at 20 °C	843,0	kg/m ³	EN ISO 12185
Colour	hellbgelb		VISUELL
Viscosity at 100 °C	8,5	mm ² /s	DIN 51562-1
Viscosity at 40 °C	43,1	mm ² /s	DIN 51562-1
Viscosity Index VI	178		DIN ISO 2909
Brookfield Viscosity at -40 °C	52.500	mPa*s	ASTM D2983
Pourpoint	-39	°C	DIN ISO 3016
Flashpoint	234	°C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1b		ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.

04.03.2022