



the lifeblood of your car



1L | 1151155-001

RAVENOL SCOOTER 4-Takt Fullsynth.

Kategorie: 2 stroke engine oil

Artikelnummer: 1151155

Specification: API SN

Oil type: Fully synthetic

Recommendation: Aprilia, Arctic Cat, Argo, Bombardier, Dinli, Honda, Kawasaki, Peugeot, Piaggio, Polaris, Suzuki, Yamaha

RAVENOL SCOOTER 4-Takt Fullsynth. is a fully synthetic high quality green colored engine oil based on PAO for 4-stroke small engines. A specially designed additive package and a formulation with special ingredients for a high viscosity index ensure for a clean engine and clean inlet and exhaust systems and thus proper lubrication and wear protection.

RAVENOL SCOOTER 4-Takt Fullsynth. due to its special additives and the selection of base oils and its viscosity an energy-saving operation of engines. Due to its special active ingredients ensures

RAVENOL SCOOTER 4-Takt Fullsynth. for a cleaner engine and clean inlet and exhaust systems.

RAVENOL SCOOTER 4-Takt Fullsynth. is the product for optimal life of the machine. **RAVENOL SCOOTER 4-Takt Fullsynth.** ensures excellent cold start performance for optimum lubrication safety in the cold run phase.

Application Note

RAVENOL SCOOTER 4-Takt Fullsynth. is for use in 4 -Stroke engines.

Characteristics

- High wear protection
- Fuel savings through smooth running properties
- Excellent detergent and dispersant properties
- Prevention of black sludge formation
- Long life due to high oxidation stability
- Excellent cold start behavior
- Very good viscosity-temperature behavior
- Low evaporation tendency

Technical Product Data

| Property | Unit | Data | Audit |
|---------------------|-------------------------|------|-----------------|
| Colour | grün | | VISUELL |
| Sulphated Ash | 1,05 %wt. | | DIN 51575 |
| tbh | 10,5 mg KOH/g | | ASTM D2896 |
| Viscosity at 100 °C | 14,3 mm ² /s | | DIN 51562-1 |
| Viscosity at 40 °C | 85,1 mm ² /s | | DIN 51562-1 |
| Viscosity Index VI | 175 | | DIN ISO 2909 |
| Density at 20 °C | 847,0 kg/m ³ | | EN ISO 12185 |
| Flashpoint | 240 °C | | DIN EN ISO 2592 |
| Noack Volatility | 7,4 % M/M | | ASTM D5800 |
| Pourpoint | -54 °C | | DIN ISO 3016 |

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.
19.04.2022