



# RAVENOL Motobike 4-T Mineral SAE 15W-40

**Kategorie:** Motorbike engine oil

**Artikelnummer:** 1173121



**RAVENOL Motobike 4-T Mineral 15W-40** is an engine oil on mineral oil base with excellent additives which was especially produced for 4 stroke motorbikes. With **RAVENOL Motobike 4-T Mineral 15W-40** a solid and high loadable engine oil was developed for superior engines of motorbikes with wet couplings and oil lubricated couplings.

**RAVENOL Motobike 4-T Mineral 15W-40** has an excellent lubricating film adhesive capacity and a very good shear stability as well as an excellent cleaning power and a high aging resistance.

## Application Note

**RAVENOL Motobike 4-T Mineral 15W-40** is suitable as an engine oil for all motorbikes in case the specification SAE 15W-40 is requested.

1L | 1173121-001

4L | 1173121-004

20L | 1173121-020

20L | 1173121-B20

60L | 1173121-060

## Characteristics

- a very good shear stability
- very good cold start characteristics
- a high oxidation stability
- prevention of black sludge accumulation
- an excellent viscosity temperature behaviour
- suitable for catalysts
- convincing detergent and dispersant characteristics
- high safety reserves even under boundary lubrication conditions

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	863,6	kg/m <sup>3</sup>	EN ISO 12185
Colour	gelbbraun		VISUELL
Viscosity at 100 °C	14,28	mm <sup>2</sup> /s	DIN 51562-1
Viscosity at 40 °C	107,5	mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	135		DIN ISO 2909
CCS Viscosity at -20 °C	6124	mPa*s	ASTM D5293
Pourpoint	-30	°C	DIN ISO 3016
Noack Volatility	6,8	% M/M	ASTM D5800
Flashpoint	256	°C	DIN EN ISO 2592
tbn	8,0	mg KOH/g	ASTM D2896
Sulphated Ash	1,06	%wt.	DIN 51575

**Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.**

31.03.2022