

## <text>

1L | 1250100-001 4L | 1250100-004 20L | 1250100-020 RAVENOL MOTOGEAR SAE 10W-30 GL-4 Kategorie: Gear oil for manual transmissions and drive axis Artikelnummer: 1250100 Specification: API GL-4, SAE 10W-30 Oil type: Semi-synthetic Recommendation: Yamaha Application: Motorcycle

**RAVENOL MOTOGEAR SAE 10W-30 GL-4** is a semi-synthetic special multi-grade transmission fluid which is specially formulated for air and water cooled 2 and 4-stroke engines with separate gearbox lubrication.

**RAVENOL MOTOGEAR SAE 10W-30 GL-4** has an excellent lubricating film adhesion, excellent detergency and high resistance to aging.

**RAVENOL MOTOGEAR SAE 10W-30 GL-4** enables a precise and soft changing of gears. Prevents clutch slippage.

**RAVENOL MOTOGEAR SAE 10W-30 GL-4** forms a heavy-duty lubricant film, which is effective under all operating conditions.

## **Application Note**

**RAVENOL MOTOGEAR SAE 10W-30 GL-4** is designed for year-round use in all modern motorcycles of Japanese manufacturer's as YAMAHA.

## Characteristics

- Quick lubrication of the engine at all operating temperatures.
- Heavy-duty lubricant film under all operating conditions.
- Precise, soft changing of gears, no clutch slippage.
- Reliability due to excellent lubricant film adhesion, extraordinary purification capacity and outstandingageing resistance.
- Neutral towards sealing compounds.

## **Technical Product Data**

Property	Unit	Data	Audit
Density at 20 °C	858,0	kg/m³	EN ISO 12185
Colour	gelbbraun	l	VISUELL
Viscosity at 100 °C	10,3	mm²/s	DIN 51562-1
Viscosity at 40 °C	63,6	mm²/s	DIN 51562-1
Viscosity Index VI	150		DIN ISO 2909
Pourpoint	-33	°C	DIN ISO 3016
Flashpoint	230	°C	DIN EN ISO 2592
tbn	8,6	mg KOH/g	g ASTM D2896

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen. 19.04.2022