



RAVENOL LTC HOT CLIMATE-15°C Protect C12++



1L | 1410127-010

5L | 1410127-005

20L | 1410127-020

1000L | 1410127-700

Kategorie: Radiator antifreeze

Artikelnummer: 1410127

Recommendation: Chrysler MS-90032, MAN 324 Si-OAT, MB 325.5, Mopar 68163848AA, Mopar 68163849AA, Scania TB 1451, VW G 012 A8G M1, VW G 012 A8G M8, VW G 012 A8G M9, VW G 013 A8J M1, VW G 013 A8J M8, VW G 013 A8J M9, VW TL 774-G (entspricht G12++), VW TL 774-J (entspricht G13)

Application: Passenger car

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C is a ready to use, prediluted with water, eco-friendly 1.2- Ethanediol (monoethylene glycol) based coolant for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development by combining silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C protects the cooling system from rust, frost, and in summer, from overheating.

Application Note

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C** to radiator to fill line.

Characteristics

- Excellent for all-aluminium engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

Technical Product Data

| PROPERTY | UNIT | DATA | AUDIT |
|---------------------|-------------------|---------|--------------|
| Density at 20 °C | kg/m ³ | 1040,0 | EN ISO 12185 |
| Colour | | violett | VISUELL |
| pH - value at 20 °C | | 7,5 | ASTM D1287 |
| Freezing point | °C | -15 | ASTM D1177 |

All indicated data are approximate values and are subject to the commercial fluctuations.

01.08.2022