



RAVENOL EHC SAE 0W-20



1L | 1111128-001
4L | 1111128-004
5L | 1111128-005
10L | 1111128-010
20L | 1111128-020
20L | 1111128-B20
60L | 1111128-060
60L | 1111128-D60
208L | 1111128-208
208L | 1111128-D28
1000L | 1111128-700

Kategorie: Passenger car motor oil

Artikelnummer: 1111128

Viscosity: 0W-20

Specification: API SN Plus, API SP (RC), ILSAC GF-6A

Oil type: Synthetic

Approvals: API SN Plus, API SP Resource Conserving, ILSAC GF-6A

Recommendation: Buick , Cadillac, Chevrolet, Chrysler MS-6395, Ford WSS-M2C947-A, Ford WSS-M2C952-A1, GM 6094M, GM dexos1 (First Generation), Honda/Acura HTO-06, Infiniti, Lexus, Mazda, Mitsubishi, Nissan, Subaru, Suzuki, Toyota

Technology: Clean Synto®

RAVENOL EHC SAE 0W-20 is a synthetic, low-friction engine oil with CleanSynto® technology for car gasoline and diesel engines, with and without turbocharging and direct injection.

RAVENOL EHC SAE 0W-20 achieves a high viscosity index through its formulation with special base oils. The excellent cold start behavior ensures optimum lubrication safety during the cold running phase.

By a significant fuel economy **RAVENOL EHC SAE 0W-20** contributes by reducing emissions to protect the environment.

RAVENOL EHC SAE 0W-20 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

RAVENOL EHC SAE 0W-20 ensures compliance with the viscosity class even over long oil runtimes over the entire oil change interval.

Extended oil change intervals according to the manufacturer's instructions.

Application Note

RAVENOL EHC SAE 0W-20 is universal fuel-efficient engine oil, a top product for modern passenger car petrol and diesel engines. The operating instructions of the engine manufacturers must be observed.

Characteristics

- Guaranteed fastest possible lubrication of the engine
- High fuel economy (FE) effect due to the base oils and additives used
- Low volatilization tendency, thereby lower oil consumption
- Provides protection against sludging, coking, varnish and corrosion even under unfavorable operating conditions.
- No oil-related deposits in combustion chambers in the piston ring zone and on valves
- Ensures the function of the hydraulic tappets at all temperatures
- Stable engine oil, no NOx oxidation
- Good soot absorption and dispersion
- Neutral towards sealing materials

- Reduces CO2 emissions, protects the environment

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	842,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	8,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	44,2	DIN 51562-1
Viscosity Index VI		173	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	2,62	ASTM D5481
CCS Viscosity at -35 °C	mPa*s	5490	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -40 °C	mPa*s	16.800	ASTM D4684
Pourpoint	°C	-45	DIN ISO 3016
Noack Volatility	% M/M	10,4	ASTM D5800
Flashpoint	°C	232	DIN EN ISO 2592
tbn	mg KOH/g	7,8	ASTM D2896
Sulphated Ash	%wt.	0,79	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

17.03.2023