



RAVENOL RCS Racing Competition Synto SAE 5W-40



1L | 1141090-001
4L | 1141090-004
5L | 1141090-005
20L | 1141090-020
20L | 1141090-B20
60L | 1141090-060
60L | 1141090-D60
208L | 1141090-208

Kategorie: Passenger car motor oil

Artikelnummer: 1141090

Viscosity: 5W-40

Oil type: Fully synthetic

Recommendation: Rennstrecken-Partner: Empfehlung Ralf Schumacher, Rennstrecken-Partner: Hockenheim Premium Partner, Rennstrecken-Partnerschaft: Nürburgring Tested

Application: Racing

Technology: USVO®, Racing

RAVENOL RCS Racing Competition Synto SAE 5W-40 is a modern, PAO (poly-alpha-olefin) based fully synthetic multi-range engine oil with USVO® Technology.

Due to the USVO® technology we achieve an extremely high viscosity stability. We avoid the disadvantages of polymeric viscosity improvers while taking advantage of them. This improves engine protection, performance, engine cleanliness and oil drain intervals. The USVO® technology makes it possible that the product has no shear losses during the entire change interval and is extremely stable to oxidation. This unique technology helps oil to be lubricated faster, thereby minimizing friction while keeping the engine clean and efficient.

Due to the special mixture of synthetic, highly polar Group V base oils with a high proportion of high and low viscosity PAO, it could be formulated without the use of viscosity index improvers.

Due to its high viscosity index, its high HTHS value, extreme shear stability and a highly effective special novel additivation with molybdenum and tungsten, **RAVENOL RCS Racing Competition Synto SAE 5W-40** is also suitable for an extremely sporty driving style.

RAVENOL RCS Racing Competition Synto SAE 5W-40 utilizes the positive properties of molybdenum and tungsten to smooth the surface structure of the motor, reducing friction and wear, and significantly improving mechanical efficiency.

RAVENOL RCS Racing Competition Synto SAE 5W-40 achieves a secure lubrication layer thanks to its unique formulation even at very high operating temperatures, protection from corrosion (oxidation) and foaming.

Application Note

RAVENOL RCS Racing Competition Synto SAE 5W-40 is ideally suited for gasoline engines for car racing, even when subject to the highest levels of strain.

Characteristics

- Ultra-modern fully synthetic engine oil for car race with special molybdenum and tungsten additives
- Safe lubricating layer at very high operating temperatures
- High HTHS value, extreme shear stability
- Very stable and excellent viscosity behaviour
- Very low evaporation tendency
- Very good cold start characteristics
- Very good detergent and dispersant characteristics
- Protection against corrosion and foam formation

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,3	DIN 51575
tbn	mg KOH/g	10,0	ASTM D2896
Viscosity at 100 °C	mm²/s	15,03	DIN 51562-1
Viscosity at 40 °C	mm²/s	93,9	DIN 51562-1
Viscosity Index VI		168	DIN ISO 2909
CCS Viscosity at -30 °C	mPa*s	6200	ASTM D5293
Density at 20 °C	kg/m³	848,0	EN ISO 12185
Flashpoint	°C	246	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	4,26	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	18.000	ASTM D4684
Noack Volatility	% M/M	5,7	ASTM D5800
Pourpoint	°C	-57	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

08.02.2023