



- 1L | 1141091-001
- 4L | 1141091-004
- 10L | 1141091-010
- 20L | 1141091-020
- 20L | 1141091-B20
- 60L | 1141091-060
- 60L | 1141091-D60
- 208L | 1141091-208
- 208L | 1141091-D28
- 1000L | 1141091-700

RAVENOL RUP Racing Ultra Performance SAE 5W-40

Kategorie: Passenger car motor oil

Artikelnummer: 1141091

Viscosity: 5W-40

Specification: ACEA C3, API SN

Oil type: Fully synthetic

Approvals: API SN, BMW Longlife-04, GM dexos2™ (Lizenz-Nr. D20583HI081), MB-Freigabe 226.5, MB-Freigabe 229.51, Renault RN0700/RN0710, VW 511 00

Recommendation: Ford WSS-M2C917-A, Porsche C40, Rennstrecken-Partnerschaft: Nürburgring Tested, VW 502 00, VW 505 00, VW 505 01

Application: Passenger car, Racing

Technology: USVO®, Racing

RAVENOL RUP Racing Ultra Performance SAE 5W-40 was developed together with Ralf Schumacher for motorsport and is ideally suited for car racing, even when subject to the highest levels of strain. This is confirmed by his signature on the label. Although it was designed specifically as a racing oil, **RAVENOL RUP Racing Ultra Performance SAE 5W-40** has passed all necessary tests and thus received official approvals of the car manufacturers for everyday use. **RAVENOL RUP Racing Ultra Performance SAE 5W-40** offers significantly better protection for petrol and diesel engines than ordinary engine oils.

RAVENOL RUP Racing Ultra Performance SAE 5W-40 is a modern PAO (poly-alpha-olefin) based fully synthetic multigrade engine oil with special USVO® Technology.

Due to the USVO® technology we achieve an extremely high viscosity stability. We avoid the disadvantages of polymeric viscosity improvers while taking advantage of them. This improves engine protection, performance, engine cleanliness and oil drain intervals. The USVO® technology makes it possible that the product has no shear losses during the entire change interval and is extremely stable to oxidation. This unique technology helps oil to be lubricated faster, thereby minimizing friction while keeping the engine clean and efficient.

Due to the special mixture of synthetic, highly polar Group V base oils with a high proportion of high and low viscosity PAO, it could be formulated without the use of viscosity index improvers. Due to its high viscosity index, its high HTHS value, extreme shear stability and a highly effective special novel additivation with molybdenum and tungsten, **RAVENOL RUP Racing Ultra Performance SAE 5W-40** is also suitable for an extremely sporty driving style.

RAVENOL RUP Racing Ultra Performance SAE 5W-40 utilizes the positive properties of molybdenum and tungsten to smooth the surface structure of the motor, reducing friction and wear, and significantly improving mechanical efficiency.

RAVENOL RUP Racing Ultra Performance SAE 5W-40

achieves a secure lubrication layer thanks to its unique formulation even at very high operating temperatures, protection from corrosion (oxidation) and foaming.

Application Note

RAVENOL RUP Racing Ultra Performance SAE 5W-40 is ideally suited for car racing, even when subject to the highest levels of strain.

Characteristics

- Ultra-modern fully synthetic engine oil for car race with special molybdenum and tungsten additive
- Safe lubricating layer at very high operating temperatures
- High HTHS value, extreme shear stability
- Very stable and excellent viscosity behaviour
- Very low evaporation tendency
- Very good cold start characteristics
- Very good detergent and dispersant characteristics
- Good protection against corrosion and foam formation

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	846,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	14,3	DIN 51562-1
Viscosity at 40 °C	mm ² /s	87,5	DIN 51562-1
Viscosity Index VI		169	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	3,9	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	4510	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	21.300	ASTM D4684
Pourpoint	°C	-51	DIN ISO 3016
Noack Volatility	% M/M	6,0	DIN 51581
Flashpoint	°C	244	DIN EN ISO 2592
tbn	mg KOH/g	8,3	ASTM D2896
Sulphated Ash	%wt.	0,8	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

07.02.2023