



# RAVENOL ATF 8HP Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1211124

**Oil type:** Synthetic

**Recommendation:** Acura 08200-9016A, Acura ATF Type 3.0, ATF L 12108, BMW 83222289720, BMW 83222305397 (83222152426), BMW ATF 3+, Fiat 9.55550-AV5, Honda 08200-9017, Honda ATF Type 3.1, Land Rover LR023288, Land Rover LR023289, Mopar 68157995AB, Mopar 68218925AA, VW/Audi G 055 162, VW/Audi G 060 162 A2, VW/Audi G 060 162 A1, VW/Audi G 060 162 A6, ZF S671 090 312, ZF TE-ML 11 9HP28, ZF TE-ML 11 9HP48, ZF TE-ML 11 9HP50

**Application:** Passenger car



**RAVENOL ATF 8HP Fluid** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

**RAVENOL ATF 8HP Fluid** is a automatic transmission oil ATF of the latest generation for all 8 stroke automatic transmissions of ZF. It guarantees in any mode for maximum wear protection.

**RAVENOL ATF 8HP Fluid** is green colored.

## Application Note

**RAVENOL ATF 8HP Fluid** is suitable for use in automatic ZF transmission of 8HP-Series 8HP45, 8HP55, 6HP26, 8HP70, 8HP90, also for ZF transmission 6-stroke automatic 6HP-series - 6HP19X for AUDI Q7, 6HP19A, 6HP28AF. It is also suitable in ZF transmission series 9HP28, 9HP48, 9HP50.

Please observe OEM Part Numbers.

## Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against wear, corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

1L | 1211124-001

4L | 1211124-004

10L | 1211124-010

20L | 1211124-020

20L | 1211124-B20

60L | 1211124-060

60L | 1211124-D60

208L | 1211124-208

208L | 1211124-D28

1000L | 1211124-700

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	837,0	EN ISO 12185
Colour		grün	VISUELL
Pourpoint	°C	-57	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.